

DAMASCO

Interior decorative plaster with metallized effect and texture of elegant concrete or Damask steel



Main Characteristics

Description:



DAMASCO is an innovative coating in the loft design field. This is the special decorative plaster that allows creating various decorative effects with the imitation of the matte metallic, Damascus steel, metallized concrete or aged silk. The environmentally friendly material is made on the basis of acrylic, natural pigment of a pearl, granular mineral fillers and modern stabilizing additives. DAMASCO decorative plaster is the practically odorless and easy to apply. The coating has a special strength, which makes it suitable for finishing any interior spaces without restrictions.

Basic types of materials:

Cool – silver base, tinted in cold colors and shades
 Warm – light gold, tinted in warm colors and shades
 Gold – gold base, tinted in golden colors and shades

Usage:

The material is intended for finishing walls and ceilings in any interiors, restoration of old and finishing of new buildings, as well as for finishing hotels, shopping and office centers or other public spaces, and also for finishing furniture elements and stucco decoration, etc.

Preparation



Before applying the DAMASCO material, it is necessary to prepare the surface using the ORSO Infinity Basic system and/or a light preparatory putty. Surface preparation must comply with the building regulations for the preparation of walls in the interior for painting or international standards of category Q4 (K4).



NOTE: The prepared surface should be smooth and even, without scratches and chips!

1. Apply 1–2 coats of fixative of a deep penetration PRIMER NORMAL diluted with water in a ratio of 1:8. The time of interlayer drying is 2 hours. Complete drying 4–6 hours (before use, we recommend that you read the technical description of the product).
2. Apply 1 layer of a special RUVIDO substrate (before use, we recommend that you read the technical description of the product). After applying the substrate, wait for it to dry completely: 6–8 hours. The substrate gives the surface the necessary adhesion and sets the background color corresponding to the color of the DAMASCO decorative coating.



Application

The application of the DAMASCO material should be carried out with the special stainless steel spatula with rounded corners and a pointed base of the work surface. It is difficult to achieve the desired effect using another means.

The DAMASCO material is applied in 2 stages (depends on the selected effect). Apply 1 layer of DAMASCO material, covering the entire surface, leaving no gaps and gaps on the base. The application technique is classical (Venetian). Drying time of the first layer: 6–8 hours.

MetalCore and LOFT:

Apply a second layer of minimal thickness, covering the entire surface. It should be applied using the technique of vertical-horizontal strokes (criss-cross), randomly forming a texture. Immediately after applying the material (without waiting for drying), slightly smooth the surface in the direction of the strokes. This technique will allow you to create a smooth texture with light grooves – the effect of the texture of concrete. Once the material starts to dry, you can seal the surface again. This will create the aged polishing metal effect. Drying time of the second layer: 6-8 hours.



NOTE: SETA EXCLUSIVE decorative coating lends itself perfectly to local restoration.

Drying time to workload: 24 days.

Technical characteristics

Application temperature:	+5÷ +35°C
Relative humidity:	<85%
Drying by touch:	30–60 min
Interlayer drying:	6–8 h
Complete drying:	24 h
Specific gravity:	1.2–1.25 kg/l
pH:	7-8
Theoretical consumption:	3–4 m ² /kg
Color:	base typical, tinted
Packing:	0,75 kg, 4 kg, 15kg



Tinting



Tinting is possible in a wide range of colors, including support for RAL and NCS systems. We recommend tinting with the help of pigments and the PCS (PRATTA COLOR SYSTEM) tinting system according to the catalogs of own colors for silk coatings of the «SETA» series. Care should be taken when using different batches of the same color material. Mix them together to ensure uniformity of color during application.

Storage



Product without tinting in packaged form, placed in a cool, dry place, has a shelf life of up to 24 months. After use, the packaging should be carefully closed and stored in an inverted position. Storage and transportation temperature: from +5° C to +30° C.

