

## SIROCCO

Decorative paint with the effect of sand dunes



### Main Characteristics

#### Description:



Product description: SIROCCO – this is a textural decorative paint for interior and exterior works, created on the basis of acrylic copolymers with selected quartz filler and natural pearl pigment. With the help of SIROCCO, a chrome effect, light light reflection, volumetric quartz relief and stylization of textures with elements of sand ornaments are obtained. It is very easy to apply paint with a brush.

#### Basic types of materials:

Cool – silver base, painted in cold colors and shades  
 Warm – light gold, painted in warm colors and shades  
 Gold – gold base, painted in golden colors and shades

#### Usage:

The material is intended for finishing walls, ceilings in interiors and exteriors, furniture elements, restoration of old and finishing of new buildings, as well as for finishing hotels, shopping and office centers or other public spaces.

### Preparation



Before applying the ROCCIA material, it is necessary to prepare the surface using the system of preparatory putties ORSO Infinity Basic and /or Light. Surface preparation must comply with the building regulations for the preparation of walls in the interior for painting or international standards of category Q4 (K4).



**NOTE:** The prepared surface should be smooth and even, without scratches and chips!



1. Apply 1–2 coats of fixative of a deep penetration PRIMER NORMAL diluted with water in a ratio of 1:8. The time of interlayer drying is 2 hours. Complete drying 4–6 hours (before use, we recommend that you read the technical description of the product).
2. Apply 1 layer of a special PRIMER LISCIO substrate (before use, we recommend that you read the technical description of the product). After applying the substrate, wait for it to dry completely: 6–8 hours. The substrate gives the surface the necessary adhesion and sets the background color corresponding to the color of the SIROCCO decorative coating.



## Application



The SIROCCO material should be applied with a wide brush. The width of the brush depends on the ease of application and is selected independently.

The SIROCCO material is applied in 2 stages (depends on the selected effect). Apply 1 layer of SIROCCO with a brush, in circular movements, covering the entire surface, leaving no gaps and distributing the quartz filler evenly over the surface. Drying time of the first layer: 6-8 hours.

Creating the classic effect of dunes:

Apply a second layer of SIROCCO with a thickness 2 times greater than the previous one (much denser). Use a wide brush for application as well, using a cross technique, evenly distributing the material over the surface. During the distribution of the material over the surface, it will cling to the previously applied (first) layer. At the same time, forming a denser covering of the surface in places where there were already quartz particles and a less dense covering where they were not. Thus, a pleasant effect of pronounced dunes will be formed. Drying time of the second layer: 6-8 hours.

Creating the classic effect of dunes:

Apply a second layer of SIROCCO with a thickness 2 times greater than the previous one (much denser). Use a wide brush for application as well, using a cross technique, evenly distributing the material over the surface. During the distribution of the material over the surface, it will cling to the previously applied (first) layer. At the same time, forming a denser covering of the surface in places where there were already quartz particles and a less dense covering where they were not. Thus, a pleasant effect of pronounced dunes will be formed. Drying time of the second layer: 6-8 hours.



*The SIROCCO decorative coating lends itself perfectly to local restoration.*

Drying time to workload: 24 days.

## Technical characteristics

Application temperature:	+5 ÷ +35°C
Relative humidity:	< 85%
Drying by touch:	30 minutes
Interlayer drying:	4–8 h
Complete drying:	24 h
Specific gravity:	1.35–1.4 kg/l
pH:	7-8
Theoretical consumption:	6–8 m <sup>2</sup>
Color:	basic standard, tinted
Packaging:	0.75 l, 4 l, 15 l

## Tinting



Tinting is possible in a wide range of colors, including support for RAL and NCS systems. We recommend tinting with the help of pigments and the PCS (PRATTA COLOR SYSTEM) tinting system according to the catalogs of SIROCCO's own colors and for silk coatings of the «SETA» series.

Care should be taken when using different batches of the same color material. Mix them together to ensure uniformity of color during application.



## Storage



Product without tinting in packaged form, placed in a cool, dry place, has a shelf life of up to 24 months.

After use, the packaging should be carefully closed and stored in an inverted position.

Storage and transportation temperature: from +5° C (41 ° F) C to +30° C (86 ° F).

