

SHABBY

Decorative coating with silk brocade effect for interiors



Main Characteristics

Description:



SHABBY is an environmentally friendly acrylic-based decorative coating with a mother-of-pearl effect, which includes a selected quartz filler with natural pearl pigment. It has no unpleasant odor and does not contain harmful volatile substances. Silk shades and the degree of texture scuffs vary in color and intensity depending on the chosen tone and method of application.

Being versatile, SHABBY material can complement a classic interior and give it a fresh elegance suitable for any kind of design solutions. It is easy to use and does not require special skills for application. When applied, more intense accents of texture alternate with less textured areas, which allows you to create imitations of time-tested silk fabrics.

Basic types of materials:

Cold silver base, painted in cold colors and shades
 Warm – light gold, painted in warm colors and shades
 Gold – gold base, painted in golden colors and shades
 Chameleon smart base, painted in various colors and shades

Usage:

The material is intended for finishing walls and ceilings in interiors, restoration of old and finishing of new buildings, as well as for finishing hotels, shopping and office centers or other public spaces and also for finishing furniture elements and stucco decoration, etc.

Preparation



Before applying the SHABBY material, it is necessary to prepare the surface using the ORSO Infinity Basic system and/or a light preparatory putty. Surface preparation must comply with the building regulations for the preparation of walls in the interior for painting or international standards of category Q4 (K4).



NOTE: The prepared surface should be smooth and even, without scratches and chips!



1. Apply 1–2 coats of fixative of a deep penetration PRIMER NORMAL diluted with water in a ratio of 1:8. The time of interlayer drying is 2 hours. Complete drying 4–6 hours (before use, we recommend that you read the technical description of the product).
2. Apply 1 layer of a special PRIMER LISCIO substrate (before use, we recommend that you read the technical description of the product). After applying the substrate, wait for it to dry completely: 6–8 hours. The substrate gives the surface the necessary adhesion and sets the background color corresponding to the color of the SHABBY decorative coating.



Application



The application of SHABBY material should be carried out with a wide brush. The width of the brush depends on the ease of application and is selected independently.

Exclusive SHABBY material is applied in 2 stages (depends on the selected effect). Apply 1 coat of SHABBY material with a brush, in a circular motion, covering the entire surface, leaving no gaps on the base. The application technique is classical (Venetian). Drying time of the first layer: 6-8 hours.

Creating a brocade effect:



Apply a second layer of SHABBY 2 times thicker than the previous one (more tightly). Also use a wide brush for application, using the criss-cross technique, evenly distributing the material over the surface. During the distribution of the material on the surface, it will stick to the previously applied (first) layer. At the same time, forming a denser surface coating in places where there were already quartz blocks, and a less dense coating where there were none. Thus, a pleasant silk effect with scuffs is formed.

Drying time of the second layer: 6-8 hours.



The SETA EXCLUSIVE decorative coating lends itself perfectly to local restoration.

Drying time to workload: 24 days.

Technical characteristics

| | |
|--------------------------|------------------------|
| Application temperature: | +5 ÷ +35°C |
| Relative humidity: | < 85% |
| Drying by touch: | 60 min |
| Interlayer drying: | 6–8 h |
| Complete drying: | 24 h |
| Specific gravity: | 0.95–1 kg/l |
| pH: | 7-8 |
| Theoretical consumption: | 6–8 m ² |
| Color: | basic standard, tinted |
| Packaging: | 0.75 l, 4 l, 15 l |

Tinting



Tinting is possible in a wide range of colors, including support for RAL and NCS systems. We recommend tinting with the help of pigments and the PCS (PRATTA COLOR SYSTEM) tinting system according to the catalogs of own colors for silk coatings of the «SETA» series.

Care should be taken when using different batches of the same color material. Mix them together to ensure uniformity of color during application.



Storage



Product without tinting in packaged form, placed in a cool, dry place, has a shelf life of up to 24 months.

After use, the packaging should be carefully closed and stored in an inverted position.

Storage and transportation temperature: from +5° C to +30° C.

