

PHANTOM NUANCE

Matte decorative coating with a golden hue and sequins for interiors and exteriors



Main Characteristics

Description:



PHANTOM NUANCE is an elegant matte finish with a light golden hue and an unobtrusive shimmering effect, which depends both on the type of lighting in the room and on the viewing angle. Allows you to reproduce the effect of scattered diamonds on the surface of a silky matte fabric with a rare weave of golden silk threads. Ideal for finishing the surfaces of the interior and exterior walls of ancient or modern buildings of high prestige. Special components of the material provide the coating with additional abrasion resistance and washable properties.

Being versatile, the PHANTOM NUANCE material can complement a classic interior and give it a fresh elegance suitable for any kind of design solutions. It is easy to use and does not require special skills for application.

Usage:

The material is intended for finishing walls and ceilings in interiors and facades of buildings, restorations of old and finishing of new buildings, as well as for finishing hotels, shopping and office centers or other public spaces. And also for finishing furniture elements and stucco decoration, etc.

Preparation

When applied to walls and ceilings in interiors and exteriors:

Before applying the PHANTOM NUANCE material, it is necessary to prepare the surface using the system of preparatory putties ORSO Infinity Basic and /or Light. Surface preparation must comply with the building regulations for the preparation of walls in the interior for painting or international standards of category Q4 (K4).



The prepared surface should be smooth and even, without scratches and chips!



1. Apply 1–2 coats of fixative of a deep penetration PRIMER NORMAL diluted with water in a ratio of 1:8. The time of interlayer drying is 2 hours. Complete drying 4–6 hours (before use, we recommend that you read the technical description of the product).
2. Apply 1 layer of a special RUVIDO substrate (before use, we recommend that you read the technical description of the product). After applying the substrate, wait for it to dry completely: 6–8 hours. The substrate gives the surface the necessary adhesion and sets the background color corresponding to the color of the decorative PHANTOM NUANCE coating. The tinted substrate allows you to get a uniform color of the decorative coating and avoid shade differences. When choosing a color from the PHANTOM NUANCE catalog, the substrate is tinted in the same color as the decorative coating itself.



Application

Brush:



The PHANTOM NUANCE material is supplied separately from the sequins. Therefore, do not forget to add the sequins to the already colored mixture before applying. The standard proportion: 50 g of gold sequins (PRATTA GLITTER Gold) is designed for 4 liters of PHANTOM NUANCE material. However, you can adjust the contrast of sequins by changing their number per unit volume up or down. After adding the sequins to the mixture, stir it thoroughly to a homogeneous consistency so that the sequins are evenly distributed in the composition of the material.

The PHANTOM NUANCE material should be applied with a wide brush. The width of the brush depends on the ease of application and is selected independently.


The PHANTOM NUANCE material is applied in 2 stages:

1. Apply 1 coat of PHANTOM NUANCE, diluted of water on 20%, with a brush, chaotic and smooth movements, tightly covering the entire surface, leaving no gaps and irregularities from the brush. Drying time of the first layer: 6-8 hours.
2. Apply 2 layers of PHANTOM NUANCE, diluted of water on 20%, with a brush, chaotic and smooth movements, tightly covering the entire surface, leaving no gaps and irregularities from the brush. Drying time of the second layer: 4-8 hours. After drying, rinse the surface with a damp cloth in small circular movements, without much effort. This technique will give the surface a pleasant tactile effect and expose the sequins.



The PHANTOM NUANCE decorative coating lends itself perfectly to local restoration.

Spray gun application:



the material is diluted with water according to the hardware characteristics of the spray gun. Before use, we recommend that you do a trial paint job.

1. Blowout 1 layer of the PHANTOM NUANCE, tightly covering the entire surface, leaving no gaps and streaks. Drying time of the first layer: 6-8 hours.
2. Blow out the 2nd layer of the PHANTOM NUANCE, tightly covering the entire surface, leaving no gaps and streaks. Drying time of the second layer: 4-8 hours. After drying, rinse the surface with a damp cloth in small light circular movements, without much effort. This technique will give the surface a pleasant tactile effect and expose the sequins.

Drying time to operational load: 24 days.

Technical characteristics

Application temperature:	+5 – +35°C
Relative humidity:	< 85%
Drying by touch:	60 minutes
Interlayer drying:	6–8 h
Complete drying:	24 h
Specific gravity:	0.85–0.90 kg/l
pH:	7-8
Theoretical consumption:	5–6 m ² /l
Color:	basic light beige-golden, tinted
Packaging:	4 l



Tinting



Tinting is possible in a wide range of colors, including support for RAL and NCS systems. We recommend tinting using pigments and the CPS (PRATTA COLOR SYSTEM) tinting system in according to catalogs of own colors for PHANTOM series coatings (PHANTOM NUANCE section). Care should be taken when using different batches of the same color material. Mix them to ensure uniformity of color during application.

Keeping



Product without tinting in packaged form, placed in a cool, dry place, has a shelf life of up to 24 months.

After use, the packaging should be carefully closed and stored in an inverted position.

Storage and transportation temperature: from +5° C (41 ° F) C to +30° C (86 ° F).

