


BAMBI

Chalkboard effect paint



Main Characteristics

Type of product:



BAMBI - Tintable water-based paint for walls to create blackboards surface. Supplied in classic black or manufacturer's colors, also tintable white base. The result of painting is a matte surface, on which chalk adheres well. BAMBI paint is environmentally friendly, diluted with water and is virtually odorless.

Usage:

Designed for painting school boards, bar walls and bar boards, children's rooms, doors and even tables in a children's room.



The material is certified for the medical institutions

Preparation

Make sure the surface is absolutely dry and free of obvious defects.
Recommended preparation of surface is the same like for painting walls in interior.
If the surface is prepared for painting, then apply one layer of Primer Normal (previously diluted with water 1:8) and after 4-6 hours of drying, you can start application of the BAMBI paint.


Application

Brush or roller:



If necessary, dilute the paint up to 10% with water before application.
Apply two coats with a brush or roller. Time of interlayer drying is 5-6 hours.

Airless:



For application with a spray gun, BAMBI is diluted with water according to the technical specifications of the machine.



Technical characteristics

Color:	white – tintable, or RVD 0211, RVD 0247, RVD 0209, RVD 0261
Aspect:	matt
Temperature:	+ 5 C° - + 30 C°
Humidity:	up to 85%
Dilution:	material is ready to use
Touch Dry:	1 h
Recoating drying time:	5-6 h
Full dry:	24 h
Cleaning of tools:	by water
Yield:	9-10 m ² / 1 Lt
Density:	1,2 kg / Lt
Package:	0,75 Lt; 4 Lt

Tinting



Base of material is white color and can be tinted in various colors and shades according to RAL, NCS, NCP color-chart systems. When tinting exterior finishes, we recommend to use UV-resistant pigments. It is possible to differ in the shades of the applied coating from the samples presented in the catalog, as well as the difference in shades of different lots of goods. Therefore, it is necessary to mix the material from different lots and make a trial application before starting work.

Main typical fabric's colors



#RVD 0211



#RVD 0209



#RVD 0247



#RVD 0261

Storage



The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

Minimum storage temperature: + 5 °C (41 °F)

Maximum storage temperature: + 30 °C (86 °F)

