



pratta.xyz · orsochem.com · pr

UMBRELLA SILK

Acrylic based protective clear coat for silk effect decorative paints and silk effect decorative plasters.



Main Characteristics

Type of product:



UMBRELLA Silk is an interior acrylic based protective with highwater repellent properties, and protection for cooking areas. It makes silk effect surfaces washable.

Usage:

Umbrella silk is a special product for protection surfaces in interiors coated with silk effect decorative paints and plasters. It is suitable for materials as: Antico Velluto, Dolce Seta, Damasco Burroso, Shabby, Seta Exclusive, Pura Seta 800

Preparation

Before application, it is recommended to remove (by any dry method) dust and dirt from the surface. If necessary, you can wash the surface, but then dry the surface completely.

Application

Brush and Roller:





Dilute with water to 5-10% for the first and for the second layers. Wait 5-6 hours between one application and the next. We recommend to make test sample painting, before general application.




superior of the orest of the or

+7 (499) 685-45-47

pratta.xyz

+7 (499) 685-16-25







pratta.xyz · orsochem.com · pr

Technical characteristics

Color: Transperent, tinted

Aspect: matt

Temperature: $+ 5 \, \text{C}^{\circ} - + 30 \, \text{C}^{\circ}$ Humidity: up to 85%

Dilution: material is ready to use

 Touch Dry:
 1 h

 Recoating drying time:
 6-8 h

 Full dry:
 24 h

 Cleaning of tools:
 by water

 Yield:
 9-10 m² / 1 Lt

 Density:
 1-1,05 kg/Lt

 Package:
 0,75 Lt; 4 Lt

Storage





The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

Minimum storage temperature: + 5 ° C (41 ° F) Maximum storage temperature: + 30 ° C (86 ° F)

