

PRIMER LISCIO

Acrylic colorable matt primer for Interior and exterior



Main Characteristics

Description:



Wall water paint based on acrylic copolymers, pigments and micro quartz fillers. Suitable as a smooth primer for many decorative systems.

Types:

PRIMER LISCIO **P/T** – white for tinting light colours.
PRIMER LISCIO **D/A** – white for tinting dark colours.

Usage:

Suitable as base coat for: ANTICO VENEZIANO CLASSIX, SIROCCO, VELATURA, FANTASIA, METALLINE, ANTICO VELLUTO, DOLCE SETA etc.

Preparation

New Surfaces:

Make sure that the surface is completely dry and cured - no less than 4 weeks for civil plasters and 2 weeks for premixed plasters. If you need, level any imperfections with a suitable mortar for exterior; then sand and clean the surfaces. Apply 1 coat of PRIMER NORMAL and, after 4-6 hours proceed by painting with two coats of PRIMER LISCIO following the technical instructions below.

Painted Surfaces:

Remove old peeling paint residues and, if necessary, fill and smooth any imperfections with a suitable mortar for exterior; then sand and clean the surfaces. Apply 1 coat of PRIMER NORMAL and, after 4-6 hours proceed by painting with two coats of PRIMER LISCIO following the technical instructions below.


Application

Brush and Roller:



Dilute with water to 20-25% both for the first and for the second hand. Wait 5-6 hours between one application and the next.

Airless:



When airless spraying, thinning varies depending on the equipment used and the pressure.



Technical characteristics

Temperature for application:	+5 ÷ +35 °C
Humidity:	< 85%
Touch Drying:	30 minutes
Drying between layers:	4-6 hours
Complete drying:	24 hours
Density:	1,6–1,65 kg/l
pH:	6.5 ÷ 8
Theoretical Yield:	8 ÷ 10 m ² /L
Colour:	White and colour chart
Packing:	0,75 Lt, 4 Lt, 15 Lt.

Precautionary

The product must be transported, used and stored in accordance with the standards in force regarding hygiene and safety. Let the residues dry out completely and treat them as special waste. Consult the safety data sheet for additional information.

Storage



The product should be preferably used within 2 years from date of manufacture when stored in original unopened containers and in appropriate temperature conditions.

Minimum storage temperature: + 5 ° C (41 ° F)
Maximum storage temperature: + 30 ° C (86 ° F)

